

## SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: TERGITOL™ TMN-10 (90% AQ) SURFACTANT

Issue Date: 04/16/2015 Print Date: 04/18/2015

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

#### 1. IDENTIFICATION

Product name: TERGITOL™ TMN-10 (90% AQ) SURFACTANT

#### Recommended use of the chemical and restrictions on use

**Identified uses:** Multi-purpose surfactant. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

#### **COMPANY IDENTIFICATION**

THE DOW CHEMICAL COMPANY 2030 WILLARD H DOW CENTER MIDLAND MI 48674-0000 UNITED STATES

**Customer Information Number:** 

800-258-2436

SDSQuestion@dow.com

#### **EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact**: 800-424-9300 **Local Emergency Contact**: 800-424-9300

#### 2. HAZARDS IDENTIFICATION

#### Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Skin irritation - Category 2 Serious eye damage - Category 1

Label elements Hazard pictograms



Signal word: DANGER!

#### **Hazards**

Causes skin irritation.

Causes serious eye damage.

#### Precautionary statements

#### Prevention

Wash skin thoroughly after handling. Wear eye protection/ face protection.

Wear protective gloves.

#### Response

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

#### Other hazards

Slipping hazard.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Chemical nature: Alcohol Alkoxylate

This product is a mixture.

Component	CASRN	Concentration
Poly(oxy-1,2-ethanediyl), .alpha[3,5-dimethyl-1-(2-methylpropyl)hexyl]omegahydroxy-	60828-78-6	>= 87.0 %
Water	7732-18-5	<= 10.0 %
Poly(ethylene oxide)	25322-68-3	<= 3.0 %

## 4. FIRST AID MEASURES

#### Description of first aid measures

**General advice:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

**Skin contact:** Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

**Eye contact:** Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: No emergency medical treatment necessary.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Chemical eye burns may require extended irrigation. Obtain prompt
consultation, preferably from an ophthalmologist. No specific antidote. Treatment of exposure should
be directed at the control of symptoms and the clinical condition of the patient.

#### 5. FIREFIGHTING MEASURES

**Suitable extinguishing media:** To extinguish combustible residues of this product use water fog, carbon dioxide, dry chemical or foam.

Unsuitable extinguishing media: no data available

#### Special hazards arising from the substance or mixture

**Hazardous combustion products:** Under fire conditions some components of this product may decompose. The smoke may contain unidentified toxic and/or irritating compounds. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** This material will not burn until the water has evaporated. Residue can burn.

#### Advice for firefighters

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. To extinguish combustible residues of this product use water fog, carbon dioxide, dry chemical or foam.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Evacuate area. Refer to section 7, Handling, for additional precautionary measures. Only trained and properly protected personnel must be involved in clean-up operations. Keep upwind of spill. Ventilate area of leak or spill. Spilled material may cause a slipping hazard. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Page 3 of 11

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Sand. Dirt. Do not use water for cleanup. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

## 7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin, and clothing. Do not swallow. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Conditions for safe storage: No specific requirements. Additional storage and handling information on this product may be obtained by calling your sales or customer service contact. The shelf life given is for unopened containers stored under moderate temperature conditions.

Storage stability

Shelf life: Use within 24 Month

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Poly(ethylene oxide)	US WEEL	TWA aerosol	10 mg/m3

#### **Exposure controls**

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

## Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Avoid gloves made of: Polyvinyl alcohol ("PVA"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Page 4 of 11

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Issue Date: 04/16/2015

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed: however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Physical state Liquid. Color Yellow Odor pungent

Odor Threshold No test data available

pΗ 6.4 Calculated.

Melting point/range Not applicable to liquids

Freezing point See Pour Point

Boiling point (760 mmHg) > 100 °C ( > 212 °F) Calculated. Flash point closed cup Not applicable 0.7 Calculated. Similar to water

**Evaporation Rate (Butyl Acetate** 

= 1)

Flammability (solid, gas) Not applicable to liquids Lower explosion limit No test data available Upper explosion limit No test data available

**Vapor Pressure** 15 mmHg at 20 °C (68 °F) Calculated. Relative Vapor Density (air = 1) 0.6 Calculated. (based on water)

1.042 at 20 °C (68 °F) / 20 °C Calculated. Relative Density (water = 1)

Water solubility 100 % Visual Partition coefficient: nno data available

octanol/water

**Auto-ignition temperature** No test data available **Decomposition temperature** No test data available **Dynamic Viscosity** 95.864 mPa.s Calculated.

92 cSt at 25 °C (77 °F) Calculated. **Kinematic Viscosity** 

**Explosive properties** no data available Oxidizing properties no data available Molecular weight no data available Molecular formula Not applicable (mixture)

-16 °C (3 °F) Calculated. pour point

NOTE: The physical data presented above are typical values and should not be construed as a specification.

#### 10. STABILITY AND REACTIVITY

Reactivity: no data available

Chemical stability: Thermally stable at typical use temperatures.

Possibility of hazardous reactions: Polymerization will not occur.

**Conditions to avoid:** Do not distill to dryness. Product can oxidize at elevated temperatures. Some components of this product can decompose at elevated temperatures.

Incompatible materials: Avoid contact with: Strong acids. Strong oxidizers.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Ketones. Organic acids.

## 11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

#### **Acute toxicity**

#### Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for a similar material: Estimated. LD50, Rat, > 5,000 mg/kg

### Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): estimated

LD50, Rabbit, > 4,000 mg/kg

#### Acute inhalation toxicity

Vapors are primarily water; single exposure is not likely to be hazardous.

As product: The LC50 has not been determined.

#### Skin corrosion/irritation

Prolonged contact may cause severe skin irritation with local redness and discomfort.

May cause more severe response on covered skin (under clothing, gloves).

Page 6 of 11

#### Serious eye damage/eye irritation

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

#### Sensitization

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

## Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

## Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

## Carcinogenicity

No relevant data found.

#### **Teratogenicity**

No relevant data found.

#### Reproductive toxicity

No relevant data found.

#### Mutagenicity

No relevant data found.

#### **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

### COMPONENTS INFLUENCING TOXICOLOGY:

#### <u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-</u> Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. For narcotic effects: No relevant data found.

The LC50 has not been determined.

#### Poly(ethylene oxide)

#### Acute inhalation toxicity

Typical for this family of materials. LC50, Rat, 6 Hour, dust/mist, > 2.5 mg/l No deaths occurred at this concentration.

## 12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

## **Toxicity**

## Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 103 mg/l, OECD Test Guideline 203 or Equivalent

#### Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), static test, 48 Hour, 164.9 mg/l, OECD Test Guideline 202 or Equivalent

## Toxicity to bacteria

IC50, Bacteria, 16 Hour, > 1,000 mg/l

#### Poly(ethylene oxide)

## Acute toxicity to fish

For this family of materials:

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 > 100 mg/L in the most sensitive species tested).

#### Persistence and degradability

## Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-

**Biodegradability:** Biodegradation under aerobic static laboratory conditions is moderate (BOD20 or BOD28/ThOD between 10 and 40%).

Theoretical Oxygen Demand: 2.2 mg/mg

Chemical Oxygen Demand: 2.05 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
10 d	3 %
20 d	33 %

#### Poly(ethylene oxide)

**Biodegradability:** For this family of materials: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail Biodegradation: 48 % Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Theoretical Oxygen Demand: 1.67 - 1.77 mg/mg

Biological oxygen demand (BOD)

Page 8 of 11

Incubation Time	BOD
5 d	0 - 17 %
10 d	3 - 56 %
20 d	39 - 77 %

Bioaccumulative potential

Bioaccumulation: No data available for this product.

Mobility in soil

No data available.

#### 13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed. permitted: Incinerator or other thermal destruction device. Waste water treatment system.

### 14. TRANSPORT INFORMATION

DOT

Environmentally hazardous substance, liquid, n.o.s.(Poly(oxy-Proper shipping name

1,2-ethanediyl), .alpha,-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-

.omega.-hydroxy-)

**UN** number

UN 3082 Class 9 Packing group Ш

Marine pollutant Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-

methylpropyl)hexyl]-.omega.-hydroxy-

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk according to Annex I or II of MARPOL 73/78 and the **IBC or IGC Code** 

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

#### 15. REGULATORY INFORMATION

#### **OSHA Hazard Communication Standard**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute Health Hazard Chronic Health Hazard

## Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

#### California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances knownto the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

#### United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

## 16. OTHER INFORMATION

#### **Product Literature**

Additional information on this and other products may be obtained by visiting our web page. Additional information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure.

## Hazard Rating System NFPA

Page 10 of 11

Health	Fire	Reactivity
3	1	0

#### Revision

Identification Number: 101234230 / A001 / Issue Date: 04/16/2015 / Version: 6.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this

document.

Legend

TWA	8-hr TWA
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

#### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.